

SS-666

80mm Thermal Printer

- Elegant and fashionable appearance
- Alarm at paper release
- Japanese cutter, long lifetime



I/O Interfaces



- ① RJ12 ② USB
- ③ Ethernet ④ COM
- ⑤ DC-in

SS-666 Thermal Printer

Printer Ability	
Printing Method	Direct Thermal
Printing Speed	260mm/s
Effective Printing Width	72mm
Paper Width	80 mm±0.5mm

Printing Support	
Self-defining Character	Support
Barcode 1D	UPC-A; UPC-E; EAN-13; EAN-8; CODE39; CODE93; CODABAR; ITF25; CODE128
Barcode 2D	PDF417; QRCODE; Data Matrix
Interface	Serial + USB + Lan
Support Functions	Sound alarm, lack paper alarm, black label detection, over-heat protection, cutter wrong position detection, top cover not tight detection
Cash Drawer Control	DC24V, 1A, 6 wire RJ-11 plug

Paper Specifications	
Paper Type	Thermal roll paper 80×Ø 80mm
Paper Thickness	0.06mm ~ 0.08mm
Loading Method	Simple to install
Cutting Method	Original Auto Cut from Japan

Environmental	
Working	Temperature: 5 ~ 50°C, humidity: 10 ~ 80%
Storage	Temperature: -20 ~ 60°C, humidity: 10 ~ 90%

Lifetime	
Reliability	Movement reliability 150 km, cutter lifetime 1,000,000 times