

SP-TL21

1", 2" label size available

Automatic label peeling

Compatible with CPCL, ESC/POS, TSC command set



SPECIFICATION:

Printing Method	Thermal Line
Resolution	8 dots/mm (203dpi) , 384 dots/line
Printing Speed	Max 127mm/s, General 101mm/s
Effective Printing Width	Max 56mm
Paper Width	57mm±0.5mm
Printing Head Temp Detection	Yes
Paper-out Sensor	Yes
Self-defined character	Yes
Graph Printing	Diagram, downloaded bitmap supported
Print Font	Codepage.: ANK: 9 x17 / 12 x24; Chinese: 24 x 24
Barcode	1D: UPC-A; UPC-E; EAN-13; EAN-8; CODE39; CODE93; CODABAR; ITF25; CODE128
	2D: QR CODE, PDF417, DATA MATRIX
Interface	RS232+USB+Bluetooth
Other Functions	Paper-out alarm, Black-mark detection, Over-heat protection, Buzzer
Cash Drawer	DC12V, 1A, 6pin RJ-11 socket
Power supply	DC12V±10%, 2A
Paper Type	Normal thermal paper: Max 57×Ø80mm, Min 57×Ø25mm
Paper Thickness	0.06mm~0.14mm
Paper Supply Method	Drop-in easy paper loading
Paper Cutting Method	Manual , Auto-peel (label paper)
Operating Temp/Humidity	0 ~ 50°C/10 ~ 80%
Storage Temp/Humidity	-20 ~ 60°C/10 ~ 90%
TPH	100 km



www.sop-pos.com



sales@sop-pos.com



086 969 899