

SP-TL24

1", 2" label size available

Support label printing and receipt printing

High Cost-effective

New popular appearance



SPECIFICATION:

Printing Method	Thermal Line
Resolution	8 dots/mm (203dpi), 384 dots/line
Printing Speed	Max 127mm/s
Effective Printing Width	48mm/56mm
Paper Width	20-60mm
Paper Type	Label paper, receipt paper
Paper-out Sensor	Yes
Self-defined character	Yes
Graph Printing	Diagram, downloaded bitmap supported
Print Font	ASCII: 9 x17 /8 x 16 / 12 x24; Chinese: 24 x 24, 16 x 16
Barcode	1D: UPC-A; UPC-E; EAN-13; EAN-8; CODE39; CODE93; CODABAR; ITF25; CODE128 2D: QR CODE, PDF417, DATA MATRIX
Interface	USB
Other Functions	Paper-out alarm, Over-heat protection, Paper house cover open and close alarm, Buzzer
Outer Dimension	239*180*161mm(L*W*H) Weight: 1902g(paper roll excluded)
Power supply	DC12V±10%, 2A
Paper roll diameter	Max.Ø80mm
Paper Thickness	Normal paper: 0.06mm~0.08mm, label paper: 0.12~0.14mm
Paper Supply Method	Drop-in easy paper loading
Paper Cutting Method	Manual
Operating Temp/Humidity	0 ~ 50°C/10 ~ 80%
Storage Temp/Humidity	-20 ~ 60°C/10 ~ 90%
TPH	100 km