

Thermal Label Printing Scales HLS1000

Feature

PLU Programmable Data:

LFCode,Item name,Item No.,unit price,charge unit,Fresh days,Tare Weight ,barcode,department,packing weight,packing type(normal ,fixed weight,fixed price,fixed weight and fixed price),Info One,Info Two,Label format,discount,hotkey

Specification

Max capacity	15KG
Accuracy	2/5g
Verification Scale Interval	2/5g, 5g, 5/10g, 10g
Mini-mun Capacity	40g, 100g,100g, 200g
Display	Two Line LCD 256*32 dot matrix display
Weighting digit	5 digit
Unit price digit	8 digit
Total price digit	8 digit
Keyboard	
Type	Mylar Button
Number	140 buttons (28 function keys , 112*2 hot keys)
Data Storage	Store 10000PLU,can set at most 112 hot keys
Printing Speed	80mm/s
Interface	RS232 + TCP/IP
Power Supply	AC100~240V,50/60Hz
Dimension(L*W*H)	437mm * 372mm * 523mm
Label Paper Size	Width: 30~60mm, Maximen otter diameter100mm, Maxi mun inner Diameter 40mm
Paper Out Method	Tear or Strip
Temperature	Working: 0~40℃ Storage: -20~70℃
Humidity	Working: 20-85% Storage: 5-95%

Accuracy Class	III
Executive Standard	GB/T 7722-2005

Picture

