

SOPPOS SS-3008		
Picture		
Picture		
Performance Parameter		
Image (pixels)	1280 pixels(H)*800 pixels(v)	
Light Source	Aiming:617 nm LED ; illumination:6500K LED	
Scanning Distance	40-200mm @ UPC/EAN 13mil PCS=90%; 20-250mm @ QR 20mil PCS=100%	
Image Resolution	≥ 5mil	
Minimum Print Contrast	≥ 25% (UPC/EAN 100%)	
Barcode Sensitivity	Pitch	±65°
	Roll	±30°
	Skew	±55°
Barcode Types	<p>1D: UPC/EAN/JAN,UPC-A & UPC-E,EAN-8 & EAN-13, JAN-8 &JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128,Code 93, Interleaved 2 of 5 (ITF),Addendum 2 of 5, IATA Code,MSI/Plessey, China Postal Code,Code 32 (Italian Pharmacode),RSS 14,RSS Limited, RSS Expanded</p> <p>2D: QR Code, Data Matrix, PDF417,Aztec, Maxicode, Hanxin code, etc.</p>	
Data Interface Port	RJ-45	
Mechanical and Electric Performance		
SIZE(Length x Width x Height)	173mm*67mm*94mm	
Weight (without cable)	220g	
Indicator	Beeper and LED Light	
Communication interface	HID USB、 USB Virtual COM、 RS-232	
Input voltage	5VDC±10%	
Working Current	170mA	
Working parameters		
Environmental Parameter		
Storage Temperature	-40°C ~ 60°C	
Working Temperature	0°C ~ 50°C	
Relative Humidity	5% ~ 95%	
Drop Resistance	5M	
IP Rating	IP52	
Certificates		
CE,RoHS,EMC,LVD, ISO9001:2008, ISO14001:2004		